

ENTRY PARKING STAND TIR

CATALOG SHEET



Parking stand is used for giving parking tickets from roll with capacity of 3000 tickets, reading, evaluating and viewing data from parking card and for communication with operator. It displays base information on colourful display and by automatic voice message. It manages entry barrier. From this stand there is a connected and managed barrier for enter and the protective elements. The parking stand communicates by TCP/IP protocol with server

Mechanic construction:

- The stand is made of 1,5 mm thick steel galvanized sheet, colour RAL7016, (anthracite grey), plexi-glass front panel

Dimensions:

- 280 x 210 x 1400 mm

Weight:

- 35 kg

Standard specification:

- Parking ticket printer
- Abonent parking card reader (usually MIFARE)
- Two-line backlit 20-character display
- Control unit with minicomputer, Linux operating system
- I / O board
- Intercom button
- Voice messages
- Heating device managed by thermostat

Extension:

- The second printer of parking tickets, capacity of hopper is 3000 tickets
- Bar code reader
- RFID sticker reader with read distance up to 3 m
- Camera for recording of car driver
- LPR camera
- I / O board for connecting of another devices
- Transmitter for connecting readers to read a third-party card

Technical Specifications:

- Power supply: 230 VAC, 50 Hz,
- Fuse: 16A / 1B
- Power consumption with heating: 850 VA
- Cover: IP43 / 20
- Operating temperature: -20 ° C to +50 ° C
- Mounting: on a base plate or concrete foundation

Identifying media:

Parking card is used for charging short-term parking fees and for abonent identification. Usually it is Mifare, or there is possibility to use another kind of identification card.

RFID sticker, dimensions 92 x 24 x 0,2 mm, frequency 860 – 960 MHz is used for distant identification of vehicles, read distance is up to 5 m.

TRITON SYSTEMS Sp. z o. o

Trylińskiego 2 Street

10-683 Olsztyn

phone: 89 612 09 23

e-mail: biuro@tritonsystems.pl