

EXIT PARKING STAND TOF

CATALOG SHEET



Parking stand is used for checking parking tickets, reading, evaluating and viewing data from parking card and communication with operator. It displays base information on colourful display and by automatic voice message. It manages exit barrier. From this stand there is a connected and managed barrier for exit and the protective elements. The parking stand communicates by TCP/IP protocol with server

Checks parking tickets fanfold 145g, with dimensions 85,6 x 54 mm

Mechanical construction:

- The stand is made of 1,5 mm thick steel galvanized sheet, colour RAL7016, (anthracite grey), plexi-glass front panel

Specification:

- Dimensions: 1400 x 280 x 350 mm
- Weight: 50 kg
- Bar code reader
- Abonament parking card reader (usually MIFARE)
- Two-lined backlit 20-characters display
- Control unit with minicomputer, Linux operating system
- I/O board
- Ticket issuing button
- Intercom button
- Voice messages
- Heating device managed by thermostat

Extension:

- 6 "coloured display
- Tickets with bar code removal
- Bar code reader
- RFID Tag reader with read distance up to 3 m
- Camera for recording of car driver
- LPR camera
- I/O board for connecting of another devices
- Payment on exit terminal via contactless bank card (optionally PIN pad)

Technical specification:

- Power supply: 230 VAC, 50 Hz,
- Fuse: 16A / 1B
- Power consumption with heating: 850 VA
- Cover: IP43 / 20
- Operating temperature: -20 °C to +50 °C
- Mounting: on base plate or concrete foundation

Identifying media:

Parking card is used for charging short-term parking fees and for abonent identification. Usually it is Mifare/Legic, or there is possibility to use another kind of identification card

RFID sticker, dimensions 92 x 24 x 0,2 mm, frequency 860 – 960 MHz is used for distant identification of vehicles, read distance is up to 5m

TRITON SYSTEMS Sp. z o.

Trylińskiego 2 Street

10-683 Olsztyn

phone: 89 612 09 23

e-mail: biuro@tritonsystems.pl